

PacketCable™ 1.5 Specifications

Management Event MIB Specification

PKT-SP-EVEMIB1.5-I02-050812

ISSUED

Notice

This PacketCable specification is a cooperative effort undertaken at the direction of Cable Television Laboratories, Inc. (CableLabs®) for the benefit of the cable industry. Neither CableLabs, nor any other entity participating in the creation of this document, is responsible for any liability of any nature whatsoever resulting from or arising out of use or reliance upon this document by any party. This document is furnished on an AS-IS basis and neither CableLabs, nor other participating entity, provides any representation or warranty, express or implied, regarding its accuracy, completeness, or fitness for a particular purpose.

© Copyright 2004-2005 Cable Television Laboratories, Inc.
All rights reserved.

Document Status Sheet

Document Control Number:	PKT-SP-EVEMIB1.5-I02-050812			
Document Title:	Management Event MIB Specification			
Revision History:	D01 – Released September 30, 2004			
	I01 – Issued January 28, 2005			
	I02 – Issued August 12, 2005			
Date:	August 12, 2005			
Status:	Work in Progress	Draft	Issued	Closed
Distribution Restrictions:	Author Only	CL/Member	CL/Member/Vendor	Public

Key to Document Status Codes:

- Work in Progress** An incomplete document, designed to guide discussion and generate feedback, that may include several alternative requirements for consideration.
- Draft** A document in specification format considered largely complete, but lacking review by Members and vendors. Drafts are susceptible to substantial change during the review process.
- Issued** A stable document, which has undergone rigorous member and vendor review and is suitable for product design and development, cross-vendor interoperability, and for certification testing.
- Closed** A static document, reviewed, tested, validated, and closed to further engineering change requests to the specification through CableLabs.

TRADE MARKS:

DOCSIS®, eDOCSIS™, PacketCable™, CableHome®, CableOffice™, OpenCable™, OCAP™, CableCARD™, M-CMTS™ and CableLabs® are trademarks of Cable Television Laboratories, Inc.

Contents

1	SCOPE	1
1.1	Introduction and Overview	1
1.2	Purpose of document	1
1.3	Organization of document.....	1
1.4	Requirements	1
2	REFERENCES	2
2.1	Normative.....	2
2.2	Informative	2
2.3	Reference Acquisition	2
3	TERMS AND DEFINITIONS	3
4	ABBREVIATIONS AND ACRONYMS	3
5	PACKETCABLE MANAGEMENT EVENT MIB	4
	APPENDIX A ACKNOWLEDGEMENTS	15
	APPENDIX B REVISION HISTORY	16

This page left blank intentionally

1 SCOPE

1.1 Introduction and Overview

The Management Event MIB provides a common data and format definition for events (informative, alarm, etc.). It also specifies by what means events are transmitted. Use of a common event mechanism facilitates management of the MTA in a multi-vendor environment and provides a standard means to implement PacketCable™ specified events.

1.2 Purpose of document

This document describes an SNMP MIB in SMIV2, to support the management event mechanism as described in [1]. It is intended to be implemented in the MTA and management devices.

1.3 Organization of document

The Management Event MIB defined in this document provides a set of objects required for the management of PacketCable compliant MultiMedia Terminal Adapter (MTA) devices. The mechanisms to control the event reporting are defined in this specification.

This MIB itself is structured as six groups:

- Management information that controls the event reporting (pktcDevEventControl).
- Management information that configures the reporting of the various programmable events (pktcDevEventConfig).
- Management information that configures the event throttling control (pktcDevEventThrottle).
- Management information that configures that allows the retrieval of events via SNMP (pktcDevEventLocal).
- Management information that specifies the information sent in traps and informs (pktcDevEventNotify).
- Management information that defines the trap and inform messages (pktcDevEventNotification).

1.4 Requirements

Throughout this document, the words that are used to define the significance of particular requirements are capitalized. These words are:

- | | |
|------------|--|
| "MUST" | This word or the adjective "REQUIRED" means that the item is an absolute requirement of this specification. |
| "MUST NOT" | This phrase means that the item is an absolute prohibition of this specification. |
| "SHOULD" | This word or the adjective "RECOMMENDED" means that there may exist valid reasons in particular circumstances to ignore this item, but the full implications should be understood and the case carefully weighed before choosing a different course. |

"SHOULD NOT"	This phrase means that there may exist valid reasons in particular circumstances when the listed behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
"MAY"	This word or the adjective "OPTIONAL" means that this item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because it enhances the product, for example; another vendor may omit the same item.

2 REFERENCES

2.1 Normative

In order to claim compliance with this specification, it is necessary to conform to the following standards and other works as indicated, in addition to the other requirements of this specification. Notwithstanding, intellectual property rights may be required to use or implement such normative references.

- [1] PacketCable 1.5 Management Event Mechanism, PKT-SP-MEM1.5-I02-050812, August 12, 2005, Cable Television Laboratories, Inc.
- [2] IETF RFC 1034/STD0013, Domain names - concepts and facilities, November, 1987.
- [3] IETF RFC 2578/STD0058, Structure of Management Information Version 2 (SMIv2), April 1999.
- [4] IETF RFC 2579, Textual Conventions for SMIv2, April 1999.
- [5] IETF RFC 2580/STD0058, Conformance Statements for SMIv2, April 1999.
- [6] IETF RFC 3550, RTP: A Transport Protocol for Real-Time Applications, July 2003.
- [7] PacketCable 1.5 MTA Device Provisioning Specification, PKT-SP-PROV1.5-I02-050812, August 12, 2005, Cable Television Laboratories, Inc.

2.2 Informative

- [8] PacketCable 1.5 MTA MIB, PKT-SP-MIB-MTA1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.
- [9] PacketCable 1.5 Signaling MIB, PKT-SP-MIB-SIG1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.
- [10] PacketCable 1.5 Network-Based Call Signaling Protocol Specification, PKT-SP-NCS1.5-I02-050812, August 12, 2005, Cable Television Laboratories, Inc.
- [11] PacketCable 1.5 Security Specification, PKT-SP-SEC1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.

2.3 Reference Acquisition

- Cable Television Laboratories, Inc., 858 Coal Creek Circle, Louisville, CO 80027; Phone 303-661-9100; Fax 303-661-9199; Internet: <http://www.cablelabs.com>
- Internet Engineering Task Force (IETF) Secretariat c/o Corporation for National Research Initiatives, 1895 Preston White Drive, Suite 100, Reston, VA 20191-5434, Phone 703-620-8990, Fax 703-620-9071, Internet <http://www.ietf.org/>

3 TERMS AND DEFINITIONS

This PacketCable specification uses the following terms and definitions:

Endpoint	A Terminal, Gateway or MCU
-----------------	----------------------------

4 ABBREVIATIONS AND ACRONYMS

This PacketCable specification uses the following abbreviations:

E-MTA	Embedded MTA – a single node which contains both an MTA and a cable modem.
FQDN	Fully Qualified Domain Name. Refer to IETF RFC 1594 for details.
IANA	Internet Assigned Numbered Authority. See www.ietf.org for details.
IETF	Internet Engineering Task Force. A body responsible, among other things, for developing standards used in the Internet.
IP	Internet Protocol. An Internet network-layer protocol.
MAC	Media Access Control. It is a sublayer of the Data Link Layer. It normally runs directly over the physical layer.
MTA	Multimedia Terminal Adapter.
OSS	Operations Systems Support. The back office software used for configuration, performance, fault, accounting and security management.
SNMP	Simple Network Management Protocol.

5 PACKETCABLE MANAGEMENT EVENT MIB

The PacketCable 1.5 Management Event MIB MUST be implemented as defined below.

```

PKTC-EVENT-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    NOTIFICATION-TYPE,
    BITS
        FROM SNMPv2-SMI
    DateAndTime
        FROM SNMPv2-TC
    clabProjPacketCable
    SnmpAdminString
        FROM CLAB-DEF-MIB
    OBJECT-GROUP,
    MODULE-COMPLIANCE,
    NOTIFICATION-GROUP
        FROM SNMPv2-CONF
    ifPhysAddress
    InetAddressType,
    InetAddress,
    InetPortNumber
        FROM INET-ADDRESS-MIB ;

pktcEventMib MODULE-IDENTITY
    LAST-UPDATED "200508120000Z" -- August 12, 2005
    ORGANIZATION "Cable Television Laboratories, Inc"
    CONTACT-INFO
        "Sumanth Channabasappa
        Postal: Cable Television Laboratories, Inc.
        858 Coal Creek Circle
        Louisville, Colorado 80027
        U.S.A.
        Phone: +1 303-661-9100
        Fax: +1 303-661-9199
        E-mail: mibs@cablelabs.com"

    DESCRIPTION
        "This MIB module supplies the basic management objects
        for event reporting

        Acknowledgements:
            Eugene Nechamkin - Broadcom Corp
            John Berg - CableLabs, Inc.
            Kevin Marez - Motorola, Inc.
            Satish Kumar - Texas Instruments
            Venkatesh Sunkad - CableLabs, Inc."

    ::= { clabProjPacketCable 3 }

--
--
pktcDevEventControl OBJECT IDENTIFIER ::= { pktcEventMib 1 }
pktcDevEventThrottle OBJECT IDENTIFIER ::= { pktcEventMib 2 }
pktcDevEventStatus OBJECT IDENTIFIER ::= { pktcEventMib 3 }
pktcDevEventDescr OBJECT IDENTIFIER ::= { pktcEventMib 4 }
pktcDevEventLog OBJECT IDENTIFIER ::= { pktcEventMib 5 }
pktcDevEvNotification OBJECT IDENTIFIER ::= { pktcEventMib 6 }
--
---
--- Event Reporting control objects
---
pktcDevEvControl OBJECT-TYPE
    SYNTAX BITS {
        resetEventLogTable(0),
        resetEventDescrTable(1)

```



```
    }    MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "This MIB object defines the actions related to the event
    log configuration.

    The MTA MUST take the appropriate action whenever
    a bit is set to a value of '1'.

    Setting the resetEventLogTable(0) bit to
    a value of '1' clears the entire event log
    (Deletes all entries in pktcDevEventLogTable).

    Setting resetEventDescrTable(1) to a value of '1'
    resets the pktcDevEventDescrTable to the
    factory default values.

    Setting a control bit to a value of '0' MUST not result in
    any action.

    Reading this MIB object MUST always return '00'."
 ::= { pktcDevEventControl 1 }
```

```
pktcDevEvSyslogAddressType OBJECT-TYPE
SYNTAX      InetAddressType
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "This MIB Object defines the address type of the
    Syslog server.
    PacketCable devices implementing this MIB MUST
    support an InetAddressType of ipv4(1).
    PacketCable devices MAY optionally implement other
    address types.

    If an unsupported InetAddressType is used to set
    this object, the PacketCable device MUST reject it
    and report an SNMP error stating 'wrong value'.

    If an SNMP SET results in a type that does not match
    the value contained in the MIB Object
    pktcDevEvSyslogAddress, the PacketCable device MUST
    reject the SNMP SET with an 'inconsistent value'
    error."
 ::= { pktcDevEventControl 2 }
```

```
pktcDevEvSyslogAddress OBJECT-TYPE
SYNTAX      InetAddress
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "This MIB Object contains the IP address of the
    Syslog server. If this is set to either 0.0.0.0 or
    255.255.255.255 the device MUST inhibit syslog
    transmission.
    The use of FQDNs is syntactically allowed, but
    discouraged since a failure to resolve them in a
    timely manner may leave the device without access to
    the Syslog daemon during critical network events.
    The type of address this object represents is defined
    by the MIB Object pktcDevEvSyslogAddressType.

    If an SNMP SET results in a type that does not match
    that indicated by the MIB Object
    pktcDevEvSyslogAddressType, the PacketCable device MUST
    reject the SNMP SET with an 'inconsistent value'
    error."
```

```

 ::= { pktcDevEventControl 3 }

pktcDevEvSyslogUdpPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This MIB Object contains the UDP Port Number of the Syslog
        Server. The PacketCable device must send the Syslog
        messages to this port on the Syslog Server."
    DEFVAL { 514 }
    ::= { pktcDevEventControl 4 }

--
-- Event throttling control
--

pktcDevEvThrottleAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
        unconstrained(1),
        maintainBelowThreshold(2),
        stopAtThreshold(3),
        inhibited(4)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION

        "This MIB Object controls the throttling of the
        transmitted messages upon generation of an event
        (SNMP/Syslog).

        A value of unconstrained(1) causes event messages
        to be transmitted without regard to the threshold
        settings.

        A value of maintainBelowThreshold(2) causes event
        messages to be suppressed if the number of transmissions
        would otherwise exceed the threshold.
        A value of stopAtThreshold(3) causes event message
        transmission to cease at the threshold, and not
        resume until directed to do so.

        A value of inhibited(4) causes all event message
        Transmission to be suppressed.

        An event causing both an SNMP and a Syslog message
        is still treated as a single event.

        Writing to this object resets the thresholding state.

        Refer to MIB Objects pktcDevEvThrottleThreshold and
        pktcDevEvThrottleInterval for information on throttling."
    DEFVAL { unconstrained }
    ::= { pktcDevEventThrottle 1 }

pktcDevEvThrottleThreshold OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This MIB Object contains the number of events per
        pktcDevEvThrottleInterval to be transmitted before
        throttling."

```

An event causing both a SNMP and a syslog message is still treated as a single event."

```
DEFVAL { 2 }
 ::= { pktcDevEventThrottle 2 }
```

pktcDevEvThrottleInterval OBJECT-TYPE

```
SYNTAX      Unsigned32
UNITS       "seconds"
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
```

"This MIB Object contains the interval over which the throttle threshold applies." DEFVAL { 1 }

```
 ::= { pktcDevEventThrottle 3 }
```

-- Status Reporting

pktcDevEvTransmissionStatus OBJECT-TYPE

```
SYNTAX      BITS {
              syslogThrottled(0),
              snmpThrottled(1),
              validSyslogServerAbsent(2),
              validSnmpManagerAbsent(3),
              syslogTransmitError(4),
              snmpTransmitError(5)
            }
```

```
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"This MIB Object reflects the status of the event transmission.

If a bit corresponding to a state is set to a value of:

```
'1', it indicates that the state is true
'0', it indicates that the state is false
```

'Event throttling' is based on thresholds and the current setting of pktcDevEvThrottleAdminStatus.

'Server/Manager' indicators must be based on the availability of valid Syslog server/SNMP managers.

'Transmit Errors' must only be used in cases where the PacketCable Device can identify unavailable servers."

```
 ::= { pktcDevEventStatus 1 }
```

-- Event Descriptions

pktcDevEventDescrTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF PktcDevEventDescrEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"This MIB table contains all the possible events that can be generated by the device. This includes

```

    both PacketCable defined and vendor-specific events."
 ::= { pktcDevEventDescr 1 }

pktcDevEventDescrEntry OBJECT-TYPE
    SYNTAX      PktcDevEventDescrEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table is created for each
         event the PacketCable Device implementing this
         MIB is capable of reporting."
    INDEX { pktcDevEventDescrId, pktcDevEventDescrEnterprise }
    ::= { pktcDevEventDescrTable 1 }

PktcDevEventDescrEntry ::= SEQUENCE {
    pktcDevEventDescrId      Unsigned32,
    pktcDevEventDescrEnterprise Unsigned32,
    pktcDevEventDescrFacility INTEGER,
    pktcDevEventDescrLevel  INTEGER,
    pktcDevEventDescrReporting BITS,
    pktcDevEventDescrText   SnmpAdminString
}

pktcDevEventDescrId OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This MIB Object contains the event identifier for the
         specific event to which the priority and display
         strings belong.
         The event identifier can either be PacketCable defined
         or vendor-specific."
    ::= { pktcDevEventDescrEntry 1 }

pktcDevEventDescrEnterprise OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object provides the IANA enterprise number of
         the Organization defining the event. Thus, all PacketCable
         defined events will contain the CableLabs IANA enterprise
         number and for vendor-specific events it will contain
         the IANA enterprise number of the defining organization."
    ::= { pktcDevEventDescrEntry 2 }

pktcDevEventDescrFacility OBJECT-TYPE
    SYNTAX      INTEGER {
        kernel(0),
        user(1),
        mail(2),
        daemon(3),
        auth(4),
        syslog(5),
        lpr(6),
        news(7),
        uucp(8),
        cron(9),
        authPriv(10),
        ftp(11),
        ntp(12),
        security(13),
        console(14),
        clockDaemon(15),
        local0(16),
    }

```

```

        local1(17),
        local2(18),
        local3(19),
        local4(20),
        local5(21),
        local6(22),
        local7(23)
    }
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "This MIB Object contains the facility
    for the event.
    For PacketCable events this MUST be set to
    local0(16)."
```

```
 ::= { pktcDevEventDescrEntry 3 }
```

```

pktcDevEventDescrLevel OBJECT-TYPE
SYNTAX INTEGER {
    emergency(0),
    alert(1),
    critical(2),
    error(3),
    warning(4),
    notice(5),
    info(6),
    debug(7)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "This MIB Object contains the priority level that
    is controlled by this entry.
    The levels are described as:

    emergency(0) - A condition that makes the system unusable.
    alert(1) - A service-affecting condition for which
    immediate action must be taken.
    critical(2) - A service-affecting critical condition.
    error(3) - An error condition.
    warning(4) - A warning condition.
    notice(5) - A normal but significant condition.
    info(6) - An informational message.
    debug(7) - A debug message."
```

```
 ::= { pktcDevEventDescrEntry 4 }
```

```

pktcDevEventDescrReporting OBJECT-TYPE
SYNTAX BITS {
    local(0),
    syslog(1),
    snmpTrap(2),
    snmpInform(3)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "This MIB Object defines the action to be taken on
    occurrence of this event class.

    Setting a bit to a value of '1' indicates that the
    corresponding action will be taken upon occurrence of
    this event, provided the required parameters are present.
    (e.g.: Syslog Server for Syslog messages, SNMP targets for
    SNMP traps and SNMP INFORMs etc). If none of the bits
    are set then no action is taken upon occurrence of the
    event."
```

The default value of this MIB Object is dependent on the value of the MIB Object 'pktcDevEventDescrLevel', for the corresponding event.

For the following values of 'pktcDevEventDescrLevel':
 emergency(0), alert(1), critical(2) and error(3),
 the PacketCable device MUST set the bits for local(0),
 syslog(1) and snmpInform(3) to a value of '1' and the rest
 to a value of '0'.

For all the remaining values of 'pktcDevEventDescrLevel',
 the PacketCable device MUST set the bits for local(0) and
 syslog(1) to a value of '1' and the rest to a value of
 '0'."

```
 ::= { pktcDevEventDescrEntry 5 }

pktcDevEventDescrText OBJECT-TYPE
    SYNTAX      SnmpAdminString(SIZE (0..127))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This MIB Object contains event display
        string providing a human-readable description of the
        event."
    ::= { pktcDevEventDescrEntry 6 }

---
-- Events generated
---
pktcDevEventLogTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PktcDevEventLogEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This MIB table contains a log of the events
        generated by the PacketCable device.
        A description of all the events that can be
        generated by the device can be obtained from the
        MIB table 'pktcDevEventDescrTable'."
    ::= { pktcDevEventLog 1 }

pktcDevEventLogEntry OBJECT-TYPE
    SYNTAX      PktcDevEventLogEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry in this table describes an event that
        has occurred, indexed in the chronological order of
        generation. The details of the event are borrowed
        from the parameters associated with the corresponding
        event entry in 'pktcDevEventDescrTable', at the
        time of the event generation.
        While all entries created as such can be cleared using
        the MIB Object pktcDevEvControl, the Event entries
        themselves cannot be individually deleted."

    INDEX { pktcDevEvLogIndex }
    ::= { pktcDevEventLogTable 1 }

PktcDevEventLogEntry ::= SEQUENCE {
    pktcDevEvLogIndex      Unsigned32,
    pktcDevEvLogTime       DateAndTime,
    pktcDevEvLogEnterprise Unsigned32,
    pktcDevEvLogId         Unsigned32,
    pktcDevEvLogText       SnmpAdminString,
    pktcDevEvLogEndpointName SnmpAdminString,
```

```

pktcDevEvLogType          BITS,
pktcDevEvLogTargetInfo   SnmpAdminString,
pktcDevEvLogCorrelationId Unsigned32,
pktcDevEvLogAdditionalInfo SnmpAdminString
}

```

```

pktcDevEvLogIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object provides relative ordering of the
        objects in the event log.
        This object will always increase except when
        (a) the log is reset via pktcDevEvControl,
        (b) the device reboots and does not implement non-volatile
        storage for this log,
        (c) it reaches the value 2^31.
        The next entry for all the above cases is 0.
        This also serves as an indicator of event sequence."
 ::= { pktcDevEventLogEntry 1 }

```

```

pktcDevEvLogTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object provides a human-readable description
        of the time at which the event occurred."
 ::= { pktcDevEventLogEntry 2 }

```

```

pktcDevEvLogEnterprise OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object provides the IANA enterprise number of
        the Organization defining the event. Thus, all PacketCable
        defined events will contain the CableLabs IANA enterprise
        number and for vendor-specific events it will contain
        the IANA enterprise number of the defining organization."
 ::= { pktcDevEventLogEntry 3 }

```

```

pktcDevEvLogId OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object contains the event identifier for the
        specific event to which the priority and
        display strings belong.
        The event identifier can either be PacketCable defined
        or vendor-specific."
 ::= { pktcDevEventLogEntry 4 }

```

```

pktcDevEvLogText OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object contains the contents of
        pktcDevEventDescrText, corresponding to the event, at

```

the moment of generation."
 ::= { pktcDevEventLogEntry 5 }

pktcDevEvLogEndpointName OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This MIB Object provides the endpoint identifier followed by the PacketCable MTA's Fully Qualified Domain Name (FQDN) and the IP Address (IP) of the PacketCable MTA device.

This will be denoted as follows:

aaln/n:<FQDN>/<IP>, where 'n' is the Endpoint number.

or

<FQDN>/<IP> if it is not specific to an endpoint."

::= { pktcDevEventLogEntry 6 }

pktcDevEvLogType OBJECT-TYPE

SYNTAX BITS {
 local(0),
 syslog(1),
 trap(2),
 inform(3)
 }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This MIB Object contains the kind of actions taken by the PacketCable device when the event under consideration occurred.

A bit with a value of 1 indicates the corresponding action was taken. Setting it to a value of 0 indicates that the corresponding action was not taken.

An event may trigger one or more actions (e.g.: Syslog and SNMP) or may remain as a local event since transmissions could be disabled or inhibited as defined by the Throttle MIB Objects."

::= { pktcDevEventLogEntry 7 }

pktcDevEvLogTargetInfo OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This MIB Object contains a comma separated list of the actions taken, along with the target IP address for the generated event.

The syntax is as:

<action-1/IP:port>,<action-2/IP:port>,<action-3/IP:port>

Where <action-n/IP> is to be denoted as follows:

For Syslog events:

syslog/<IP address of the Syslog Server:port>

For SNMP traps:

snmpTrap/<IP address of the SNMP Server:port>

For SNMP INFORMS:

snmpInform/<IP address of the SNMP Server:port>

If there are multiple targets for the same type (SNMP


```

        Traps sent to multiple IP addresses) or if there are
        multiple messages sent to the same IP (Syslog and SNMP
        sent to the same IP address) they need to be reported
        individually."
 ::= { pktcDevEventLogEntry 8 }

pktcDevEvLogCorrelationId OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        " This MIB Object contains the correlation ID
        generated by the MTA as per section 5.4.5 of [7] that
        was being used by the MTA when the event
        was generated."
 ::= { pktcDevEventLogEntry 9 }

pktcDevEvLogAdditionalInfo OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This MIB Object contains additional, useful
        information in relation to the corresponding event that a
        PacketCable device might wish to report (for example:
        parameterized data or debugging information). The format
        is vendor-specific.
        However, the PacketCable device is not required to
        implement this functionality."
 ::= { pktcDevEventLogEntry 10 }

---
-- Notifications
---

pktcDevEvNotificationIndex OBJECT IDENTIFIER ::=
    { pktcDevEvNotification 0 }

pktcDevEvInform NOTIFICATION-TYPE
    OBJECTS {pktcDevEvLogIndex, pktcDevEvLogTime,
    pktcDevEvLogEnterprise,pktcDevEvLogId,
    pktcDevEvLogEndpointName,pktcDevEvLogCorrelationId,ifPhysAddress}
    STATUS      current
    DESCRIPTION
        "This Notification MIB Objects contains the Inform
        contents for event reporting "
 ::= { pktcDevEvNotificationIndex 1 }

pktcDevEvTrap NOTIFICATION-TYPE
    OBJECTS {pktcDevEvLogIndex, pktcDevEvLogTime,
    pktcDevEvLogEnterprise,pktcDevEvLogId,
    pktcDevEvLogEndpointName,pktcDevEvLogCorrelationId,ifPhysAddress}
    STATUS      current
    DESCRIPTION
        "This Notification MIB Objects contains the Trap contents
        for event reporting "
 ::= { pktcDevEvNotificationIndex 2 }

---
-- Conformance/Compliance
---

pktcEventConformance OBJECT IDENTIFIER ::= { pktcEventMib 7 }
pktcEventCompliances OBJECT IDENTIFIER ::= { pktcEventConformance 1 }
pktcEventGroups      OBJECT IDENTIFIER ::= { pktcEventConformance 2 }

```

```

pktcEventBasicCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
    "The compliance statement for devices that implement
    Event reporting feature."
  MODULE     --pktcEventMib

MANDATORY-GROUPS {
    pktcEventGroup,
    pktcEventNotificationGroup
}
-- units of conformance
 ::= { pktcEventCompliances 3 }

pktcEventGroup OBJECT-GROUP
  OBJECTS {
    pktcDevEvControl,
    pktcDevEvSyslogAddressType,
    pktcDevEvSyslogAddress,
    pktcDevEvSyslogUdpPort,
    pktcDevEvThrottleAdminStatus,
    pktcDevEvThrottleThreshold,
    pktcDevEvThrottleInterval,
    pktcDevEvTransmissionStatus,
    pktcDevEventDescrEnterprise,
    pktcDevEventDescrFacility,
    pktcDevEventDescrLevel,
    pktcDevEventDescrReporting,
    pktcDevEventDescrText,
    pktcDevEvLogIndex,
    pktcDevEvLogTime,
    pktcDevEvLogEnterprise,
    pktcDevEvLogId,
    pktcDevEvLogText,
    pktcDevEvLogEndpointName,
    pktcDevEvLogType,
    pktcDevEvLogTargetInfo,
    pktcDevEvLogCorrelationId,
    pktcDevEvLogAdditionalInfo
  }

  STATUS      current
  DESCRIPTION
    "Group of MIB objects for PacketCable Management Event
    MIB."
  ::= { pktcEventGroups 1 }

pktcEventNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS { pktcDevEvInform, pktcDevEvTrap }
  STATUS      current
  DESCRIPTION
    "Group of MIB objects for notifications related to
    change in status of the MTA Device."
  ::= { pktcEventGroups 2 }
END

```

Appendix A Acknowledgements

On behalf of CableLabs and its participating member companies, we would like to extend a heartfelt thanks to all those who contributed to the development of this specification. Certainly all the participants of the provisioning focus team have added value to this effort by participating in the review and weekly conference calls. Particular thanks are given to:

Eugene Nechamkin (Broadcom)
Paul Duffy (Cisco Systems)
Rick Vetter (Motorola, Inc.)
Wim De Ketelaere (tComLabs)
Peter Bates (Telcordia)
Satish Kumar (Texas Instruments)
Kevin Marez (Motorola, Inc.)
Roy Spitzer (Telogy/TI)

John Berg, Jean-Francois Mule, Sumanth Channabasappa, Venkatesh Sunkad (CableLabs, Inc)

Appendix B Revision History

The following ECN was incorporated in PKT-SP-EVEMIB1.5-I02-050812.

ECN	Date Approved	Summary
EVEMIB1.5-N-05.0282-1	7/13/05	Event MIB Objects definitions clarification